VICE							
JP11039755	in in the second se	·					
1999-02-12		*****	.= .	·.· ·.			
FUJIMOTO BUNICHI; O	NAKA KATS	UFUMI					
FUJITSU LTD; FUJITSU	J SHUHENKI	KK			ļ		
<u>JP11039755</u>		 			; ;		
JP19970189425 199707	715		•		1 1		
1			· ; ; ;				
G11B15/68 ; G11B17/22	2 ; G11B19/0.	2 ; G11B27	7/00				
	• • • •		., :.	• • • •			
	Abstrac	:t					
y automatically detecting i jed after the installation, o vice is furnished with plur for performing the specifi	it, when the lil or the like. ral frames F1- fied process. I	brary devic -F4 and an Each of the	e is new accesse frames	vly insta or 23 m s F1-F4	lled or the noving to is provide	e frame position ed with	s of each frame
	JP11039755 1999-02-12 FUJIMOTO BUNICHI; O FUJITSU LTD; FUJITSU JP11039755 JP19970189425 19970 G11B15/68; G11B17/22 COLVED: To enable a library automatically detecting ed after the installation, ovice is furnished with plur for performing the specif	JP11039755 1999-02-12 FUJIMOTO BUNICHI; ONAKA KATSI FUJITSU LTD; FUJITSU SHUHENKI JP11039755 JP19970189425 19970715 G11B15/68; G11B17/22; G11B19/02 Abstract OLVED: To enable a library device itsely automatically detecting it, when the like of after the installation, or the like vice is furnished with plural frames F1-for performing the specified process.	JP11039755 1999-02-12 FUJIMOTO BUNICHI; ONAKA KATSUFUMI FUJITSU LTD; FUJITSU SHUHENKI KK JP11039755 JP19970189425 19970715 G11B15/68; G11B17/22; G11B19/02; G11B27 Abstract OLVED: To enable a library device itself to recogy automatically detecting it, when the library device after the installation, or the like vice is furnished with plural frames F1-F4 and an for performing the specified process. Each of the	JP11039755 1999-02-12 FUJIMOTO BUNICHI; ONAKA KATSUFUMI FUJITSU LTD; FUJITSU SHUHENKI KK JP11039755 JP19970189425 19970715 G11B15/68; G11B17/22; G11B19/02; G11B27/00 Abstract OLVED: To enable a library device itself to recognize or automatically detecting it, when the library device is new ed after the installation, or the like vice is furnished with plural frames F1-F4 and an access for performing the specified process. Each of the frames	JP11039755 1999-02-12 FUJIMOTO BUNICHI; ONAKA KATSUFUMI FUJITSU LTD; FUJITSU SHUHENKI KK JP11039755 JP19970189425 19970715 G11B15/68; G11B17/22; G11B19/02; G11B27/00 Abstract OLVED: To enable a library device itself to recognize or update a utomatically detecting it, when the library device is newly instated after the installation, or the like vice is furnished with plural frames F1-F4 and an accessor 23 m for performing the specified process. Each of the frames F1-F4	JP11039755 1999-02-12 FUJIMOTO BUNICHI; ONAKA KATSUFUMI FUJITSU LTD; FUJITSU SHUHENKI KK JP11039755 JP19970189425 19970715 G11B15/68; G11B17/22; G11B19/02; G11B27/00 Abstract OLVED: To enable a library device itself to recognize or update the informatically detecting it, when the library device is newly installed or the dafter the installation, or the like vice is furnished with plural frames F1-F4 and an accessor 23 moving to for performing the specified process. Each of the frames F1-F4 is provided.	JP11039755 1999-02-12 FUJIMOTO BUNICHI; ONAKA KATSUFUMI FUJITSU LTD; FUJITSU SHUHENKI KK JP11039755 JP19970189425 19970715 G11B15/68; G11B17/22; G11B19/02; G11B27/00 Abstract OLVED: To enable a library device itself to recognize or update the information of automatically detecting it, when the library device is newly installed or the frame

BEST AVAILABLE COPY

